

SPECIFICAȚII TEHNICE & PREȚURI

MOTOR

Tip	OHC - Parallel Twin, unicam 270°
Capacitate cilindrica	755 cc
Diametru x Cursa	87 x 63.5 mm
Raport compresie	11.0 : 1
Putere maxima	91,8 CP / 9.500 rot/min
Cuplu maxim	75 Nm / 7.250 rot/min
Viteza maxima	205 km/h
Capacitate ulei	3.9 litri

SISTEM DE ALIMENTARE

Tip	PGM-FI - Injectie electronica
Capacitate rezervor	16.9 litri (inclusiv rezerva)
Consum carburant WMTC*	4.35 l/100km

EMISII CO2 & NOMA DE POLUARE

Norma poluare	Euro 5
Emisii Co2	103 g/km

SISTEM ELECTRIC

Sistem de aprindere	Gestionat electronic
Demaror	Electric
Lumini	LED
HISS (Honda Intelligent Security System)	Standard

TRANSMISIE

Tip	Manuala in 6 trepte
Ambreiaj	Multi-disc, umed, Slipper Clutch
Transmisie finala	Lant cu O-ring

DORĂRI

Ride by wire & Riding Modes	
Honda Selectable Torque Control (HSTC)	
Furca Showa USD (SFF-CA) - 43mm	
Display Digital – TFT	
Lumini Full LED	
Priza USB C	
Semnalizatoare cu auto-cancel	

CULORI DISPONIBILE

MAT BALLISTIC BLACK METALLIC



MAT IRIDIUM GRAY METALLIC



ROSS WHITE



De la **11.550 €** (TVA inclus)*

2 Ani Asistență Rutieră Honda



SUSPENSIE & ROȚI

Tip	Fata	Furca telescopica Showa USD (SFF-CA), 43mm (cursa 200 mm)
	Spate	Amortizor monoshock cu brat Pro-Link (cursa 190 mm)
Jante	Fata	21M/C
	Spate	18M/C
Anvelope	Fata	90/90-R21 M/C 54H
	Spate	150/70-R18 M/C 70H

SISTEM DE RĂNARE

Fata	Dublu disc hidraulic 310 x 4.5 mm, axial, etrier 4 pistoane (ABS)
Spate	Disc 256 x 6 mm, hidraulic, etrier mono-piston (ABS)

CADRU

Tip	Diamond - Otel
Dimensiuni (L x l x t)	2,325 x 838 x 1,450 mm
Ampatament	1,560 mm
Unghi inclinare furca	27°
Cursa	111 mm
Inaltime sa	850 mm
Garda la sol	210 mm
Masa proprie	208 kg

* Preturile in lei se vor calcula la cursul afisat in showroom. Dealerul isi rezerva dreptul de a modifica preturile afisate, fara nicio informare prealabila. Imaginile sunt cu titlu de prezentare.